



S10 - MICROPNP LIGHT SENSOR

PRODUCT DESCRIPTION

The MicroPnP™ Light Sensor (**S10**) detects the level of ambient light in lumens.

MICROPNP PERIPHERALS

MicroPnP Peripherals are self-identifying sensors and actuators that connect to MicroPnP Wireless Devices to provide plug-and-play sensing and control.

The MicroPnP software automatically installs and configures all drivers, eliminating the cost and complexity of deploying an IoT network.

Note: only one peripheral of this type may be connected to a MicroPnP Wireless Device.

APPLICATIONS

The light sensor supports environmental sensing. Applications include:

- ★ Workplace monitoring
- ★ Monitoring of animal enclosures
- ★ Smart lighting systems
- ★ Weather monitoring systems
- ★ Monitoring compliance with perishable goods storage

CORE COMPONENTS

The **S10** is based on the VEML6040 from Vishay®, for more information please visit:

[Vishay_VEML6040.pdf](#)

S10 CHARACTERISTICS

Characteristic	Value	Unit
Min/Max light intensity	0/16496	lx
Min/Max temperature	-40/85	°C
Accuracy light intensity	+/- 0.01	lx
Min/Max period between updates	10 / 86400	s
Avg current: period = 1hour	42	nA
Avg current: period = 60s	2.5	μA
Avg current: period = 10s	15	μA

Note: avg current values represent the current that this sensor draws from a MicroPnP Wireless Device that is configured with the noted update period. This value excludes message transmission.

RELATED PRODUCTS

Item **S10** requires a MicroPnP Wireless Device such as **Pxx** or **Lxx**. This item is compatible with all items in the MicroPnP catalog:

versasense.com/files/VersaSense-Catalog.pdf

INFORMATION/SUPPORT

Web: www.versasense.com

Sales: sales@versasense.com

Help: support@versasense.com

Other: info@versasense.com

Post: VersaSense NV, Kapeldreef 60, 3001 Leuven, Belgium.