



S24 - VERSASENSE CURRENT LOOP INTERFACE

PRODUCT DESCRIPTION

The VersaSense Current Loop Interface (**S24**) provides the ability to read values from the industry standard 4-20mA analog current loop. It uses an external power supply that can feed loop consumers while also powering the device eliminating battery drain. Various loop configurations are possible to allow flexibility in connecting to the actual sensor.

VERSASENSE SENSORS

VersaSense Sensors are self-identifying sensors and actuators that connect to VersaSense Wireless Devices to provide plug-and-play sensing and control.

The VersaSense software automatically installs and configures all drivers, eliminating the cost and complexity of deploying an IoT network.

Note: only one peripheral of this type may be connected to a VersaSense Wireless Device.

APPLICATIONS

Easy and standardized monitoring of process instrumentation such as pressure, level, flow, temperature, pH or other process variables.

CORE COMPONENTS

The **S24** is based on the ATmega328 from Atmel® Microchip, for more information please visit:

[ATmega328P.pdf](#)

S24 CHARACTERISTICS

Characteristic	Value	Unit
Loop voltage	24V	V
Max. loop device current	0.5	A
Min/Max period between updates	10 / 86400	s
ADC resolution	10	bit

RELATED PRODUCTS

Item **S24** requires a VersaSense Wireless Device such as **Pxx** or **Lxx**. This item is compatible with all items in the VersaSense catalog:

[VersaSense-Catalog.pdf](#)

INFORMATION/SUPPORT

Web: www.versasense.com

Sales: sales@versasense.com

Help: support@versasense.com

Other: info@versasense.com

Post: VersaSense NV, Kapeldreef 60, 3001 Leuven, Belgium.