



S27 - VERSASENSE OXYGEN GAS SENSOR

PRODUCT DESCRIPTION

The VersaSense Oxygen Gas (O₂) Sensor (**S27**) provides the ability to measure oxygen concentrations using a dedicated gas sensor. On-board humidity, pressure and temperature sensing can be used for in-the-field calibration purposes.

VERSASENSE SENSORS

VersaSense Sensors are self-identifying sensors and actuators that connect to VersaSense Wireless Devices to provide plug-and-play sensing and control.

The VersaSense software automatically installs and configures all drivers, eliminating the cost and complexity of deploying an IoT network.

APPLICATIONS

Easy, flexible and accurate monitoring of oxygen concentrations using the SGX-4OX gas sensor. Other gas sensors can be integrated on request.

CORE COMPONENTS

The **S27** uses the SGX-4OX oxygen sensor from SGX Sensortech, for more information please visit: [SGX-4OX.pdf](#)

The **S27** has a humidity, pressure and temperature sensor on-board. This is used for increased accuracy during gas sensing.

S27 CHARACTERISTICS

Characteristic	Value	Unit
Range	0-25	% O ₂
Accuracy	0.1	% O ₂
Response time (T ₉₀)	< 15	s
Temperature range	-30 to +50	°C
Pressure range	800 to 1200	mbar
Humidity range (non-condensing)	5-95	% RH

RELATED PRODUCTS

Item **S27** requires a VersaSense Wireless Device such as **Pxx** or **Lxx**. This item is compatible with all items in the VersaSense catalog:

[VersaSense-Catalog.pdf](#)

INFORMATION/SUPPORT

Web: www.versasense.com
Sales: sales@versasense.com
Help: support@versasense.com
Other: info@versasense.com
Post: VersaSense NV, Kapeldreef 60, 3001 Leuven, Belgium.